

ToLEDo T8 CCG and AC

TOLEDO T8 V5 4FT 20W 2000LM 830
0028277



Product features

- Energy efficient and affordable LED T8 solution to replace conventional fluorescent T8 lamps • Omnidirectional 320° uniform light distribution thanks to glass tube construction design, same as traditional fluorescent T8 tubes • High lumen package - 2000lm • High lumen efficacy - 100 lm/W • Energy rating - A+ • Switching cycles - 200,000X • Average life 40,000 hours lifespan (L70 F50) • Wide beam angle - 220° • High power factor - 0.90 • Suitable for general illumination in offices, supermarkets, department stores, train stations, petrol stations, parking lots and maintenance free applications • Suitable for operation with electromagnetic gears and direct mains operation (220-240V) • 3-Year warranty.



PRODUCT OVERVIEW

IPC-kod	0028277
Produktens namn	TOLEDO T8 V5 4FT 20W 2000LM 830
Teknik	LED
Watt (klassificerad) (W)	20
Socket/Bas	G13
Generella tillämpningar	Hospitality, Logistics & Industry, Residential & Consumer,
Certifieringar	EUERL010
ETIM Class	EC001959
E-nummer FI	4740733
Ljusflöde (nominellt) (lm)	2000
Färgtemperatur (K)	3000
Färgtemperatur	Warm White
CRI (Ra)	80
Watt (nominell) (W)	20
Spänning (V)	230
Dimbart	No
Genomsnittlig (nominell) (timmar)	40000
EAN-kod	5410288282770

DATA TABLE

General data

IPC-kod	0028277
Produktens namn	TOLEDO T8 V5 4FT 20W 2000LM 830
Teknik	LED
Watt (klassificerad) (W)	20
Socket/Bas	G13
Generella tillämpningar	Hospitality, Logistics & Industry, Residential & Consumer,
Certifieringar	EUERL010
ETIM Class	EC001959
E-nummer FI	4740733

Optical data

ToLEDo T8 CCG and AC

TOLEDO T8 V5 4FT 20W 2000LM 830
0028277

Ljusflöde (nominellt) (lm)	2000
Användbart ljusflöde (klassificerat) (lm)	2000
Färgtemperatur (K)	3000
Färgtemperatur	Warm White
CRI (Ra)	80
Lumenbibehållning i slutet av nominell livslängd (lm)	70

Electrical data

Watt (nominell) (W)	20
Starttid (max) (s)	0.5
Uppvärmningstid till 60 % av fullt ljus (max) (s)	0.5
Spänning (V)	230
Lampans effektfaktor	0.9
No. Of switching cycles before premature failures	200000
Dimbart	No
Lamp Energy Label (class)	A+
kWh per 1 000 timmars brinntid	20

Lifetime data

Genomsnittlig (nominell) (timmar)	40000
Genomsnittlig livslängd (klassificerad) (h)	40000

Physical data

Vikt (kg)	0.208
-----------	-------

Packaging

Förpackningsbeskrivning	Carton
EAN-kod	5410288282770
Förpackningens enkellängd (cm)	125.5
Förpackningens enkelbredd (cm)	2.75
Förpackningens enkelhöjd (cm)	2.75
DUN14 (outer)	15410288282777
Units per outer package	10
Packaging outer length / height (cm)	129.7
Packaging outer width (cm)	22.6
Packaging outer depth (cm)	11.7

Safety data

Rengöringsinstruktioner för trasiga lampor	Not applicable
Lampa för särskilda användningsområden	No
Inte lämplig för användning i hemmet	Yes
Safety message	Suitable for totally enclosed fixture

ToLEDo T8 CCG and AC
TOLEDO T8 V5 4FT 20W 2000LM 830
0028277

